

MAP

KEYS & REMOTES

Thank you for purchasing a MAP product. Please see below instructions on how to program your replacement garage door remote to your garage door motor.

Part Number: KF910

Note: Garage remote to replace ATA PTX5 TrioCode – NOT compatible with V2

KF910 Replaces unit pictured below



Programming the KF910 to your garage door motor:

1. Press and hold the blue 'Door Code' button on the motor, or SW1 / SW2 on the receiver board.
2. Press the button on the KF910 you would like to use to control the door for two seconds.
3. Release and pause for two seconds. Press the same button again for two seconds.
4. Release the 'Door Code' or SW button. Press the KF910 button to test the operation of the door or gate.

To program remote 'Light' function:

1. Press the Light Code button & then follow steps 1-5 (above) using another button on your new remote.

Default coding type is ATA TrioCode:

Press and hold Key1 and Key2 of remote control at the same time, LED turns on, after 4 seconds, LED turns off, release the buttons, the coding type has been switched successfully.

To delete all of the remotes coded to the motor:

1. Turn off the power to the opener.
2. Press and hold the Door Code or SW1 Button.
3. Turn on the power again, while holding the button. The coding LED will illuminate to indicate that the receiver's memory has been deleted.
4. Press remote button to test the remote no longer works – all codes, including the courtesy light codes, are now erased.

WARNING! This remote contains a button/coin cell battery. If swallowed, a lithium battery can cause severe or fatal injuries within 2 hours or less. Keep batteries out of reach of children at all times whether they are new or used. If you think batteries may have been swallowed or placed inside any part of the body, seek medical attention immediately or contact the Australian Poisons Information Centre on 13 11 26 or New Zealand National Poisons Centre on 0800 764 766.

