



## **Programming instructions for KF308 / KF309**

***Please read carefully before trying to program your key. If at any time you make a mistake, start and stop your car, exit the vehicle and start the process again. The remote can only be programmed with a master key.***

- 1. Sit in the vehicle with the doors and windows closed*
  - 2. Lock doors with power door lock switch on driver's door*
  - 3. Put in and pull out key from ignition approximately 8 times or until you see the hazard / turn signal lights flash (older models lights may flash after 4 or 5 times). You need to do that in less than 10 seconds.*
  - 4. When hazard lights flash (on 2005 and newer models the gauge needles may jump a little instead) put key in ignition and turn to the ACC position (when your hazard lights flash your car is sending a signal to be received by the remote)*
  - 5. Press lock button on the new remote transmitter. Lights should flash again.*
- NOTE: If you have two remotes 1 new and 1 old or 2 new ones, please continue with steps 6 and 7.*
- 6. Press unlock button on driver's door, then lock button on driver's door. Lights will flash again.*
  - 7. Press lock button on 2<sup>nd</sup> new or old remote. Lights again will flash.*

*You are done. Exit the vehicle and try your remote. It will not work from inside the car or with the key in the ignition.*

***Note: If your hazard lights flash after inserting your key in and out, but you can't get the remote to program, you may have a dead battery or wrong remote. If instructions do not work, do it again but when you get in – shut the door, buckle seat belt and lock doors, then proceed with putting key in ignition.***

